

Safety Data Sheet

Material: 10004329

SEMICOSIL 988/1K GREY *SMP,VARIOUS

Version 2.5 (US)

Print Date 11/13/2023

Date of last alteration: 11/09/2022

1. Product and company identification

1.1 Identification of the substance or preparation:

Trade name	SEMICOSIL 988/1K GREY	*SMP,VARIOUS
Use of the Substance/Mixture	Industrial. Adhesive / sealant	

1.2 Company/undertaking identification:

Manufacturer/distributor:	Wacker Chemie AG Hanns-Seidel-Platz 4 81737 München Germany
Customer information:	Wacker Chemical Corporation 4950 S State Road Ann Arbor, MI 48108 InfoLine: Tel (517) 264-8240 Hours of operation: Monday - Friday, 8 am to 5 pm (eastern standard time) Corporate website: www.wacker.com
Emergency telephone no. (24h):	(517) 264-8500
Transportation emergency:	(800) 424-9300 (CHEMTREC, USA) (703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (GHS):

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (GHS):

No labeling according to GHS required.

2.3 Other hazards

Product can release hydrogen. Risk of hydrogen gas formation with water, alcohols, acids, metallic salts, amines and alkalis. In combination with oxygen, the released hydrogen can form oxyhydrogen. The product hydrolyses under formation of methanol (CAS-Nr. 67-56-1). Methanol is classified concerning both physical and health hazards. The hydrolysis rate and consequently the relevance for the hazard profile of the product is strongly dependent on the specific conditions.

Endocrine disrupting properties - human health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties - environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

3. Composition/information on ingredients

3.1 Chemical characterization (preparation)

Chemical characterization

Polydimethylsiloxane with functional groups and auxiliaries for addition cross-linking

Safety Data Sheet

Material: 10004329

SEMICOSIL 988/1K GREY *SMP,VARIOUS

Version 2.5 (US)

Print Date 11/13/2023

Date of last alteration: 11/09/2022

3.2 Information on ingredients:

Type	CAS-No.	Substance	Content [wt. %]		Note
			Lower	Upper	
INHA	2530-83-8	(3-(2,3-Epoxypropoxy)propyl) trimethoxysilane	>1.0	<2.0	
INHA	13463-67-7	Titanium dioxide		<0.2	C1

Type: HYD - by-product upon hydrolysis, INHA - ingredient, NEBE - by-product, MONO - residual monomer, VERU - impurity, VUL - by-product upon vulcanization. *** **Note:** C1 - IARC carcinogen, C2 - NTP carcinogen, C3 - OSHA carcinogen, NH - non-hazardous, R - reproductive toxin.

Titanium dioxide: This component does not impact the product's hazard classification. Due to the product's physical properties, particulate inhalation exposure is not possible.

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above $\geq 0.1\%$.

4. First-aid measures

4.1 General information:

Get medical attention if irritation occurs or if breathing becomes difficult. Remove contaminated clothing and shoes.

4.2 If inhaled

No special treatment required.

4.3 In case of skin contact

Remove material with a waterless skin cleaner from skin and clothing. Wash with soap and water.

4.4 In case of eye contact

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

4.5 If swallowed

If swallowed, give victim several glasses of water. If swallowed, induce vomiting.

4.6 Advice for the physician

Methanol (CAS 67-56-1) is readily and rapidly absorbed at all exposure routes and is toxic by all routes. Methanol may cause irritation of the mucosa, as well as nausea, vomiting, headaches, vertigo and visual disorders, including blindness (irreversible damage to the optic nerve), acidosis, spasms, narcosis and coma. There may be a delay in the onset of these effects after exposure.

5. Fire-fighting measures

5.1 Flammable properties:

Property:	Value:	Method:
Flash point.....	> 200 °C (> 392 °F)	(DIN 51376)
Boiling point/boiling range	not applicable	
Lower explosion limit.....	exempt	
Upper explosion limit.....	exempt	
Ignition temperature	> 400 °C (> 752 °F)	(DIN 51794)

5.2 Fire and explosion hazards:

Caution! This product is not flammable but it may evolve flammable hydrogen gas under certain conditions, which may accumulate in the container headspace. Do not use a welding or cutting torch on or near any container of this material, even if empty, because an explosion could occur. Spontaneous ignition is possible due to electrostatic discharge. The generation of hydrogen gas is increased under circumstances mentioned in Sect. 10 "Stability and reactivity". Contact with contaminated piping or vessels or with corroded and rusty containers can increase the rate of hydrogen formation. Explosion limits for hydrolysis products: 5.5-44% v/v (methanol) and 4-75.6% v/v (hydrogen).

Safety Data Sheet

Material: 10004329

SEMICOSIL 988/1K GREY *SMP,VARIOUS

Version 2.5 (US)

Print Date 11/13/2023

Date of last alteration: 11/09/2022

5.3 Recommended extinguishing media:

carbon dioxide , alcohol-resistant foam .

5.4 Unsuitable extinguishing media:

Water, dry chemical, halones.

5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide and incompletely burnt hydrocarbons .

5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus.

6. Accidental release measures**6.1 Precautions:**

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

HAZWOPER PPE Level: D**6.2 Containment:**

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

6.3 Methods for cleaning up

Scoop up large quantities after dusting surfaces with sand or Fuller's earth to prevent sticking. Sweep or scrape up the spilled material and place in an appropriate chemical waste container. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

6.4 Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Do not blend contaminated material with uncontaminated material. Do not seal collecting vessel gas-tight. Observe notes under section 7.

7. Handling and storage**7.1 Handling****Precautions for safe handling:**

Ensure adequate ventilation. Must be syphoned off in situ. Open and handle container with care. Keep container closed when not in use. Keep away from incompatible substances in accordance with section 10. Where possible, inert process equipment and blanket vessels, tanks and containers with nitrogen to reduce the available oxygen level. Contact WACKER for additional publications on the safe Handling of SiH Products. Observe information in section 8.

Precautions against fire and explosion:

Product can release hydrogen. Product can separate methanol. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Storage**Conditions for storage rooms and vessels:**

Do not store in virgin glass containers with basic surface. Observe local/state/federal regulations.

Safety Data Sheet

Material: 10004329

SEMICOSIL 988/1K GREY *SMP,VARIOUS

Version 2.5 (US)

Print Date 11/13/2023

Date of last alteration: 11/09/2022

Advice for storage of incompatible materials:

Do not store with: basic substances (e.g. alkalis, ammonia, amines), oxidizing agents, strong acids. Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

Minimum temperature allowed during storage and transportation: 5 °C (41 °F)

Maximum temperature allowed during storage and transportation: 25 °C (77 °F)

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use only with adequate ventilation.

Local exhaust:

recommended

8.2 Associate substances with specific control parameters such as limit values

Maximum airborne concentrations at the workplace:

Substance	Type	mg/m ³	ppm	Dust fract.
Methanol	OSHA PEL	260.0	200.0	
Methanol	ACGIH TWA		200.0	

Re Methanol (CAS-no. 67-56-1): STEL is 250 ppm, skin notation (ACGIH); STEL is 250 ppm, skin notation (NIOSH).

8.3 Personal protection equipment (PPE)

Respiratory protection:

In case of long or strong exposure use a NIOSH approved respirator for: organic vapors.

Hand protection:

Recommendation: butyl rubber protective gloves.

Eye protection:

chemical safety goggles.

Other protective clothing or equipment:

Recommendation: antistatic protective clothing and shoes. Provide eye bath and safety shower.

8.4 General hygiene and protection measures:

Avoid breathing dust/vapor/mist/gas/aerosol. Avoid contact with eyes and skin. Do not eat, drink or smoke when handling. Wash thoroughly after handling.

9. Physical and chemical properties

9.1 Appearance

Physical state	liquid
Form	paste
Colour	grey
Odour	faint

9.2 Safety data

Property:**Value:****Method:**

Melting point.....	not applicable	
Boiling point/boiling range	not applicable	
Flash point.....	> 200 °C (> 392 °F)	(DIN 51376)
Ignition temperature	> 400 °C (> 752 °F)	(DIN 51794)
Lower explosion limit.....	exempt	
Upper explosion limit.....	exempt	
Vapour pressure.....	exempt	
Density	1.0 g/cm ³ at 20 °C (68 °F), at 1013 hPa	
Water solubility.....	practically insoluble	
pH	Not applicable. Insoluble in water.	

Safety Data Sheet

Material: 10004329

SEMICOSIL 988/1K GREY *SMP,VARIOUS

Version 2.5 (US)

Print Date 11/13/2023

Date of last alteration: 11/09/2022

Partition coefficient: n-octanol/water: not applicable
Viscosity, dynamic.....: 450000 mPa.s at 23 °C (73 °F)
Viscosity, kinematic.....: no data available

9.3 Further information

Explosion limits for released hydrogen: 4 - 75.6%(V). Explosion limits for released methanol: 5.5 - 44%(V).

Odour Threshold: no data available
Thermal decomposition.....: > 250 °C (> 482 °F)

10. Stability and reactivity

10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

Moisture, heat, open flames, and other sources of ignition. Contact with contaminated piping or vessels or with corroded and rusty containers can increase the rate of hydrogen formation. Observe information in section 7.

10.3 Materials to avoid

Proton-active substances. Reacts with acids, basic substances (e.g. alkalis, ammonia, amines), alcohols, water, moisture, oxidizing agents, catalysts. The reaction takes place with the formation of hydrogen and methanol.

10.4 Hazardous decomposition products

Methanol by hydrolysis. Upon contact with the substances mentioned in 10: hydrogen. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.

11. Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Product details:

Exposure routes	Result/Effect
Oral	LD50 > 2000 mg/kg Species: Rat, Source: Conclusion by analogy
dermal	LD50 > 2000 mg/kg Species: Rabbit, Source: Conclusion by analogy

11.1.2 Skin corrosion/irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.3 Serious eye damage/eye irritation

Product details:

No eye irritation
(Species: Rabbit, Method: OECD 405)

11.1.4 Respiratory or skin sensitisation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Product details:

Exposure routes	Result
Inhalation	No data available.

Safety Data Sheet

Material: 10004329

SEMICOSIL 988/1K GREY *SMP,VARIOUS

Version 2.5 (US)

Print Date 11/13/2023

Date of last alteration: 11/09/2022

11.1.5 Germ cell mutagenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity - single exposure**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity - repeated exposure**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard**Assessment:**

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

11.1.11 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

11.1.12 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. Titanium dioxide has been classified by IARC as carcinogen group 2B ("possibly carcinogenic to humans").

Other information: Hydrolysis product / impurity: Methanol (CAS 67-56-1) is readily and rapidly absorbed at all exposure routes and is toxic by all routes. Methanol may cause irritation of the mucosa, as well as nausea, vomiting, headaches, vertigo and visual disorders, including blindness (irreversible damage to the optic nerve), acidosis, spasms, narcosis and coma. There may be a delay in the onset of these effects after exposure.

12. Ecological information**12.1 Toxicity****Assessment:**

Based on available data no acute effects on aquatic organisms that are relevant for classification must be expected for the product up to its limits of water solubility.

12.2 Persistence and degradability**Assessment:**

Polymer component: biologically not degradable. Elimination by adsorption to activated sludge.

12.3 Bioaccumulative potential**Assessment:**

Polymer component: No adverse effects expected.

Safety Data Sheet

Material: 10004329

SEMICOSIL 988/1K GREY *SMP,VARIOUS

Version 2.5 (US)

Print Date 11/13/2023

Date of last alteration: 11/09/2022

12.4 Mobility in soil**Assessment:**

Polymer component: insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

none known

13. Disposal considerations**13.1 Product disposal****Recommendation:**

Risk of oxyhydrogen formation upon contact with the substances mentioned in 10. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Wastes of this material should not be mixed with other wastes. Provide measures such as vented bungs to ensure pressure relief in the waste containers. Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.2 Packaging disposal**Recommendation:**

Containers may contain hazardous quantities of hydrogen gas. Uncleaned containers should not be reused to hold another material due to the potential for reaction between residual product and incompatible materials. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

14. Transport information**14.1 US DOT & CANADA TDG SURFACE**

Valuation: Not regulated for transport

Other Information: Temperature Sensitive Material.

Refrigerated transportation is required when outside temperatures are above 77F (25C) along the shipping route.

14.2 Transport by sea IMDG-Code

Valuation: Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation: Not regulated for transport

15. Regulatory information**15.1 U.S. Federal regulations****TSCA inventory status and TSCA information:**

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

Safety Data Sheet

Material: 10004329

SEMICOSIL 988/1K GREY *SMP,VARIOUS

Version 2.5 (US)

Print Date 11/13/2023

Date of last alteration: 11/09/2022

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

No SARA Hazards

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

HAPS (Hazardous Air Pollutants):

CAS-No.	Chemical	Upper limit wt. %
68187-11-1	Aluminium chromium cobalt spinels	<=0.0320
108-88-3	Toluene	<=0.0003

15.2 U.S. State regulations
California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

California Proposition 65 Carcinogens:

13463-67-7 Titanium dioxide
1333-86-4 Carbon black

This material does not contain any chemicals known to the State of California to cause reproductive effects.

Massachusetts Substance List:

This material contains no listed components.

Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan.....	ENCS (Handbook of Existing and New Chemical Substances): This product is listed in, or complies with, the substance inventory.
Australia	AIIC (Australian Inventory of Industrial Chemicals): This product is listed in, or complies with, the substance inventory.
China	IECSC (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory.
Canada.....	DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines	PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA)	TSCA (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Taiwan.....	TCSI (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA)	REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea).....	AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"): Please approach your regular contact for more detailed information.

Safety Data Sheet

Material: 10004329

SEMICOSIL 988/1K GREY *SMP,VARIOUS

Version 2.5 (US)

Print Date 11/13/2023

Date of last alteration: 11/09/2022

16. Other information

16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial Hygienists

DOT - Department of Transportation

hPa - Hectopascals

mPa*s - Milli Pascal-Seconds

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

ppm - Parts per Million

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

Flash point determination methods	Common name
---	-------------

ASTM D56.....	Tagliabue (Tag) closed cup
---------------	----------------------------

ASTM D92, DIN 51376, ISO 2592	Cleveland open cup
-------------------------------------	--------------------

ASTM D93, DIN 51758, ISO 2719	Pensky-Martens closed cup
-------------------------------------	---------------------------

ASTM D3278, DIN 55680, ISO 3679	Setaflash or Rapid closed cup
---------------------------------------	-------------------------------

DIN 51755.....	Abel-Pensky closed cup
----------------	------------------------

16.3 Conversion table:

Pressure:.....: 1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa

Viscosity:.....: 1 mPa*s = 1 centipoise (cP)